



## VP-8 8 Port Video Encoder

### The Ultimate in Enterprise Class IP Video Recording

#### Overview

- 8 channel 1U rackmount case
- All channels D1 resolution, H.264 at 30FPS
- Dual Stream
- 8 video loop-outs
- Encoder-based motion detection
- De-interlaced images
- PTZ support
- 1 channel Audio in and out
- 8 Digital Inputs and 4 Outputs



#### Technical Specifications

<b>Video/Audio Input</b>	Video Compression:	Standard H.264
	Video Input:	8-ch, BNC (1.0V p-p, 75Ω)
	Audio Compression:	OggVorbis
	Audio Input:	8-ch, BNC (2.0V p-p, 1 kΩ)
	Voice Talk Input:	1-ch, MIC connector
<b>Video/Audio Output</b>	Video Loop Out:	H.264 / MPEG4 / MJPEG
	Audio Output:	1-ch, MIC connector (2.0V p-p, 1 kΩ)
	Recording Resolution:	QCIF / CIF / 2CIF / 4CIF
	Frame Rate:	QCIF / CIF / 2CIF / 4CIF; 25(P) / 30(N)
	Video Bit Rate:	32Kps ~ 2048Kbps, or user-defined (Max. 3Mbps)
	Dual Stream:	Supported
	Stream Type:	Video / Video & Audio
<b>External Interface</b>	Network Interface:	1 RJ-45 10 / 100 / 1000 Mbps self-adaptive UTP Ethernet interface
	Serial Interface:	1 RS-485, 1 RS-232 (DB9 Port)
	Alarm In:	16
	Alarm Out:	4
<b>General</b>	Chassis:	1U, 19-inch; Rear panel provides Reset button
	Power Supply:	100 ~ 240VAC, 6.3A, 50 ~ 60Hz
	Consumption:	≤40W (without HDD)
	Working Temperature:	10% ~ 90%
	Dimensions (WxDxH):	17.32 x 11.81 x 1.77 in.
	Weight (without HDD):	≤11.02 lbs