

Overview

- 4 channel
- All channels D1 resolution, H.264 at 30FPS
- Dual Stream
- 4 video loop-outs
- Encoder-based motion detection
- De-interlaced images
- PTZ support
- 1 channel Audio in and out
- 4 Digital Input and 1 Output
- Video Insight VMS license included



Technical Specifications

| | | |
|---------------------------|------------------------|---|
| Video/Audio Input | Video Compression: | H.264 |
| | Video Input: | 4-ch, BNC (1.0V p-p, 75Ω) |
| | Audio Compression: | OggVorbis |
| | Audio Input: | 4-ch, BNC (1.0V p-p, 1 kΩ) |
| | Audio Input Interface: | BNC(2Vp-p, 1kΩ) |
| | Voice Talk Input: | 1-ch, 3.5mm audio interface (2.0V p-p, 1 kΩ) |
| Video/Audio Output | Audio Output: | 1-ch, 3.5mm audio interface (2.0V p-p, 1 kΩ) |
| | Encoding Resolution: | QCIF / CIF / 2CIF / 4CIF |
| | Frame Rate: | 25 fps (P) / 30 fps (N) |
| | Video Bit Rate: | 32 kbps ~ 2048 kbps, or user-defined (Max. 3 Mbps) |
| | Audio Bit Rate: | 64 kbps |
| | Dual Stream: | Supported |
| | Stream Type: | Video / Video & Audio |
| External Interface | Network Interface: | 1 RJ-45 10M / 100 Mbps self-adaptive UTP Ethernet interface |
| | Serial Interface: | 1 RS-485 interface (PTZ control), 1 RS-232 interface |
| | Alarm In: | 4 |
| | Alarm Out: | 2 |
| General | Power Supply: | 12 VDC power supply |
| | Consumption: | ≤8W |
| | Working Temperature: | 14°F ~ +131°F |
| | Working Humidity: | 10% ~ 90% |
| | Dimensions (DxWxH): | 7.89 x 5.35 x 1.65 in. |
| | Weight (without HDD): | ≤4.41 lbs |