

Overview

- Connectable to HD-TVI and analog cameras
- Connectable to the coaxitron camera/ with long transmission distance
- Redundant recording and holiday recording
- Manual video quality diagnostics
- VCA detection alarm (line crossing detection and intrusion detection)
- Locks and unlocks video files HDD quota and group management; different capacity can be assigned to different cameras under quota mode
- 1 self-adaptive 10M/100M/1000M network interface
- Network detection



Technical Specifications

MODEL		VP-8-V2	VP-16-V2
Video/Audio Input / Output	Video Input	8-ch	16-ch
		BNC interface	
	HDTV Video	720p/25, 720p/30, 720p/50, 720p/60, 1080p/25, 1080p/30, CVBS	
Video/Audio Encoding	Audio Input	4-ch	4-ch
		RCA (2.0 Vp-p, 1 KΩ)	
	Audio Output	1-ch, RCA (Linear, 1 KΩ)	
	Video Compression	H.264	
	Audio Compression	G.711u	
	Fram Rate	1/16 fps to real-time frame rate	
	Video Bitrate	2 Kbps to 10 Mbps	
	Audio Bitrate	4 Kbps	
	Stream Type	Video, Video & Audio	
	Main Stream	1080P/720P/WD1/4CIF/VGA/CIF	
	Dual-Stream	Support, sub-stream: WD1/4CIF (12fps), CIF/QVGA/QCIF (real-time)	
External Interface	Two-Way Audio Input	1-ch, RCA (2.0 Vp-p, 1 KΩ) (using the 1st channel of audio input)	
	Network Interface	1, RJ45 10M/100M/1000M self-adaptive Ethernet Interface	
	Series Interface	1, RS-485; half-duplex	
	Alarm In	8-ch input, 4-ch output	16-ch input, 4-ch output
	Alarm Out		
	Power Supply	12 VDC	
General	Power Consumption (with- out HDD)	≤30 W	≤45 W
	Working Temperature	-10° C to 55° C (14° F to 131° F)	
	Working Humidity	10% to 90%	
	Chassis	380 mm 1U chassis	
	Dimensions	380 mm × 290 mm × 48 mm (14.96" × 11.42" × 1.89")	
	Weight (without HDD)	≤ 2 Kg (4.41 lb)	