

# A&E SPECIFICATION

## Advidia A-14 1.3 MEGAPIXEL IR NETWORK DOME CAMERA

### 1.1 GENERAL

- A. This product shall be manufactured by a firm whose quality system is in compliance with the ISO-9001.
- B. All equipment and materials used shall be standard components that are regularly manufactured and used in the manufacturer's system.
- C. All systems and components shall have been thoroughly tested and proven in actual use.
- D. All systems and components shall be provided with comprehensive repair and spare parts replacement. The manufacturer on warranty and non-warranty items shall guarantee the spare parts and the repair.
- E. All systems and components shall have been thoroughly tested and proven in actual use.
- F. All systems and components must be in compliance with FCC, CE, UL and RoHS requirements.
- G. All materials furnished under this item shall be compliant with 802.3 Ethernet standards.

### 1.2 HD 1.3 MEGAPIXEL IR NETWORK DOME CAMERA

- A. The network camera shall offer dual video streams with up to 1.3MP resolution (1280x960) in progressive scan CMOS format, with H.264 video compression.
- B. The network camera shall provide true & day night (ICR) low-light capabilities with sensitivity down to 0.01Lux @ (F1.2, AGC ON), 0 Lux with IR.
- C. The network camera shall support Back-Light Compensation (BLC) with selectable zones.
- D. The camera shall offer video compression of H.264, MJPEG. Dual H264 streams shall be supported with independent resolution, bit rate and frame rates for the main and sub streams.
- E. The network camera shall include embedded Linux OS and support IE and client software for network preview, and be capable of performing firmware upgrades through a network using a software-based device utility or through the web interface.
- F. The network camera shall be equipped with built-in password protection which is not dependent on a server.
- G. The network camera shall support standard IT protocols including: TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, UPnP, ICMP, IGMP, SNMP, FTP, QoS.
- H. The network camera shall support industry standard Power over Ethernet (PoE) IEEE 802.3af for powering the camera over the network in addition to 12VDC local power.
- I. The camera shall provide the ability to take snapshot and record video clips from the web interface and store on the local computer.
- J. The camera shall support video motion detection with user defined areas and configurable sensitivity levels. In addition, the motion detection shall be supported by an arming schedule with the audible warning, surveillance center notification, email, ftp upload, and alarm output triggered as supported events.
- K. The camera's web interface shall permit settings to be exported to and imported from a configuration file via the web interface, API and camera manufacturer's client software.
- L. The camera shall conform to ONVIF and PSIA standards for integration with 3<sup>rd</sup> party video management systems (VMS). The camera may also support custom firmware for specific integration with a 3<sup>rd</sup> party VMS.

## A-14 1.3 MEGAPIXEL IR NETWORK DOME CAMERA

- M. The camera shall be compatible with a Video Management Software (VMS) package and Mobile Phone Application from the same manufacturer. The VMS shall not be a restricted use version of the manufacturer's full featured version.

### 1.3 POWER

- A. Power Supply 12 VDC  $\pm$  10%, PoE (802.3af)  
B. Power Consumption Max. 7 W

### 1.4 CAMERA

- A. Image Sensor 1/3" Progressive Scan CMOS  
B. Min. Illumination 0.01Lux @ (F1.2, AGC ON) ,0 Lux with IR  
C. Shutter Time 1/25s to 1/100,000s  
D. Lens 4mm@ F2.0, Angle of view: 73.1°  
E. Lens Mount M12  
F. Max. Image Resolution 1280x960  
G. Resolutions supported Main Stream: (1280 x 960, 1280 x 720)@30fps  
Sub Stream: (4CIF, CIF, VGA, QVGA)@30fps  
H. Day & Night Day, Night, Auto, Schedule  
I. Smart IR Enable or Close  
J. Sensitivity If you choose auto day/night switch, you can choose the sensitivity of the switch as high, normal and low  
K. WDR Wide dynamic range can be used when there is a high contrast of the bright area and the dark area of the scene  
L. BLC Area BLC area is the area sense the light intensity; Close, Up, Down, Left, Right and Center are selectable  
M. Back Light Compensation On/Off, Zone configurable  
N. Digital Noise Reduction Close, Normal Mode and Expert Mode are selectable  
O. Noise Reduction Level For adjusting the noise reduction level and only valid when the DNR function is enabled  
P. Image Settings Saturation, Brightness, Contrast, Sharpness  
Q. Image rotation Mirror (Left/Right, Up/Down, Center, Close)  
R. White Balance AWB1, Locked WB, Fluorescent Lamp, Incandescent Lamp, Warm Light Lamp, Natural Light

### 1.5 VIDEO & AUDIO SPECIFICATIONS

- A. Compression Main stream: H.264  
Sub stream: H.264, MJPEG  
B. Dual Stream Yes; Main stream up to 1280x960; sub-stream up to 4CIF  
C. Video Bit Rate 32 Kbps~16 Mbps  
D. Rate Control Constant, Variable  
E. H.264 profiles Main profile  
F. Max. Frame Rate(main) 30fps@1280x960, 1280x720  
G. Sub-stream 4CIF, CIF, VGA, QVGA  
H. Users  
1. Unicast Up to 6 simultaneous users  
2. Multicast Unlimited H.264  
I. Security Access Password protected  
J. Software Interface Web browser view and remote client  
K. ROI Up to 4 configurable areas

## A-14 1.3 MEGAPIXEL IR NETWORK DOME CAMERA

### 1.6 NETWORK

- |                         |                                                                                                                                                 |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| A. Alarm Trigger        | Motion detection, tampering alarm, network disconnect, IP address conflict, storage exception                                                   |
| B. Protocols            | TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour (SIP optional) |
| C. Security             | User authentication, watermark                                                                                                                  |
| D. System Compatibility | ONVIF, PSIA, ISAPI                                                                                                                              |

### 1.7 WEB BROWSER REQUIREMENTS

- |                       |                                                                                                            |
|-----------------------|------------------------------------------------------------------------------------------------------------|
| A. Operating System   | PC (Intel® Core® 2 Duo microprocessor, 2.6 GHz) with Microsoft® Windows® XP, Windows Vista®, or Windows® 7 |
| B. Web User Interface | DirectX for Windows XP, Windows Vista, Windows 7                                                           |
| C. RAM                | 2 GB                                                                                                       |
| D. Ethernet Card      | 100 Mbps                                                                                                   |
| E. Web Browser        | Internet Explorer® 7.0 or later; Firefox, Chrome                                                           |
| F. Screen Resolution  | 1024 x 768 pixels or higher, 16- or 32-bit pixel color resolution                                          |

### 1.8 PHYSICAL

- |                         |                                  |
|-------------------------|----------------------------------|
| A. Operating Conditions | -30 °C ~ 60 °C (-22 °F ~ 140 °F) |
| B. Humidity, all models | 95% or less (non-condensing)     |
| C. IR Range             | 30 meters                        |
| D. Dimension            | Φ111 × 82 (4.4" × 3.2")          |
| E. Weight               | 500g (1.1 lbs)                   |
| F. Construction         |                                  |
| a. Body Material        | Aluminum alloy                   |
| b. Body Color           | White                            |
| c. Screws               | Stainless Steel, Security Torx   |

### 1.9 CERTIFICATIONS AND RATINGS

- |                         |      |
|-------------------------|------|
| A. Regulatory           |      |
| a. IEC/EN 61000         |      |
| b. IEC/EN 55022         |      |
| c. IEC/EN 55024         |      |
| d. IEC /EN60950-1       |      |
| e. FCC Part 15, Class b |      |
| f. UL/cUL 60950-1       |      |
| g. RoHS                 |      |
| B. Ratings              |      |
| a. Ingress Protection   | IP66 |